



Brands Featured:













































EV & HEV Service Tools & Equipment





WIH-32800

80-Pc Insulated Tool Set in Rolling Tool Case

- Screwdrivers: Slotted: 2.5mm 10mm
- Phillips: #0, #1, #2, #3 Torx[®]: T6–T30 Square: #1, #2

- Terminal block: #1, #2
- Nut drivers: 7/32" 7/16", 5mm 13mm
- Sockets: 1/2" 7/8", 13mm 22mm
- T-Handles: 5/32" 3/8", 4mm 8mm L-keys: 1/2" & 10mm Pliers Cutters
- Ratchet: 3/8" drive Extension: 3/8" x 5" Cable knife: 2" (50mm)
- 2 Meter ruler: inch/metric Category IV voltage detector: 110V to 250V
- Rolling water tight tool case: 22" L x 13-3/4" W x 9" H Certified to 1000 Volt AC



WIH-32876

66-Pc Insulated Tool Set

- Screwdrivers:
- Slotted: 2mm-10mm
- Phillips: #0, #1, #2, #3 Torx®: T8–T30
- Square: #1, #2

 $\ominus \oplus$ WIH-91890

- Terminal block: #1, #2
- Nut drivers: 1/4" 7/16"
- Sockets: 1/2" 7/8". 8 22mm

• 1/4" drive, 6 pt. sockets: 5-13mm

• Open end wrenches: 8mm-13mm • 8" Tweezers • 3-Pc pliers/cutters

- Hex T-Handles: 5/32" 3/8", 4 8mm

- Ratchet: 3/8" drive
- Extension: 3/8" x 5"
- Cable knife: 2" (50mm)
- Certified to 1000 Volt AC

• Hex L-keys: 1/2" & 10mm

- Pliers
- Cutters
- Adjustable wrench



Each item in this set can also be purchased separately.







16-Pc 3/8" Drive Insulated **Ratcheting Torque Wrench** and Socket Sets

Sets include:

- Ratcheting torque wrench: 4-37 ft-lb (5-50 Nm)
- Metric or SAE sockets
- Extension bars: 5" & 10"
- Certified to 1000 Volt AC



ach item in this set can also be purchased separately

WIH-30190	SAE	1/4" – 7/8"
WIH-30192	Metric	8mm – 20mm

WIH-31391

13-Pc 1/4" Drive Insulated **Metric Socket Set**

- Sockets: 5mm 14mm
- Extensions: 2", 4"
- 1/4" Drive reversible ratchet
- Certified to 1000 Volt AC or 1500 Volt DC



WIH-31590

10-Pc 3/8" Drive Insulated **Metric Socket Set**

- Sockets: 8mm 19mm
- Extension: 5"
- 3/8" Drive reversible ratchet
- Certified to 1000 Volt AC or 1500 Volt DC

Each item in this set can also be purchased separately.



TITAN

TIT-66100

18-Pc 1/4" Drive Metric Socket Set. 1000V Insulated

- (13) Sockets: 4-14 mm
- Extensions: 2", 3", 4", 6"
- 1/4" drive reversible ratchet with quick release








16-Pc 3/8" Drive Insulated **Inch/Metric Socket Set**

- Inch sockets: 5/16" 3/4"
- Metric sockets: 8mm 19mm
- Certified to 1000 Volt AC or 1500 Volt DC







• 1/4" drive ratchet

• 2" & 4" extension bars

• 8.5" Cable stripping knife



EV & HEV Service Tools & Equipment





Insulated Extensions

• Certified to 1000 Volt AC or 1500 Volt DC

WIH-12854 1/4" x 2" WIH-12855 1/4" x 4"



eSHOK-GUARD™-1000V Socket Isolator

• Withstands impact applications

CRE-CAEAD316 1/4" Drive CRE-CAEAD324 3/8" Drive CRE-CAEAD332 1/2" Drive



CRE-CAEBH2C

eSHOK-GUARD™ - 3" Long 1000V Isolated Bit Holder

- Insulates all your standard bits up to 1000V
- 1/4" hex shank is compatible with impact drivers and drills
- Magnetic tip keeps fasteners in place





(CRESCENT)







WIH-28789

11-Pc Insulated TorqueVario-S Driver and SlimLine Blade Set

- TorqueVario-S driver: 10-50 in-lb
- SlimLine insulated blades: Slotted: 4mm, 6.5mm; Phillips: #1, #2; Square: #1, #2; Xeno: Terminal #1, #2
- Certified to 1000 Volt AC





CRE-CTVDESDS

7-Pc VDE 1000V Insulated **Screwdriver Set**

- Slotted: 1/8" x 3" , 5/32" x 4", 7/32" x 5", 1/4" x 6"
- Phillips: #0 x 3", #1 x 3", #2 x 4"





Milwaukee® 1000V Insulated Tools

- Tested and certified to UL®, OSHA, VDE & GS standards
- Dual layer insulation offers visual wear indication for tool replacement
- Flame retardant & impact resistant handle and shank
- Visible ID markings





MLW-48-22-2202

3-Pc 1000V Insulated **Screwdriver Set**

- ECX™: #1 x 4"
- Phillips: #2 x 4"
- Slotted: 1/4" x 6"





MLW-48-22-2204

4-Pc 1000V Insulated **Screwdriver Set**

- Slotted: 1/4" and 3/8" -6" and 8" long
- Phillips: #1 and #2 -3" and 4" long





MLW-48-22-2205

4-Pc 1000V Insulated **Screwdriver Set**

- Slotted: 1/4" and 3/8" -6" and 8" long
- Square: #1 and #2 - 3" and 4" long





MLW-48-22-2210

10-Pc 1000V Insulated **Screwdriver Set**

- ECX™: #1 x 4"
- Phillips: #1 x 3", #2 x 4", #3 x 6"
- Slotted: 1/4" x 6", 5/16" x 7", 3/8" x 8"
- Square: #1 x 3", #2 x 4", #3 x 6'







EV & HEV Service Tools & Equipment



Insulated T-Handle Hex Screwdriver Sets

• Certified to 1000 Volt AC

WIH-33478	5-Piece	Metric: 4mm, 5mm, 6mm, 8mm, 10mm
WIH-33490	6-Piece	Inch: $5/32$ ", $3/16$ ", $7/32$ ", $1/4$ ", $5/16$ ", $3/8$ "







KNI-98 55

1000-Volt Insulated Electrician's Dismantling Knife, 7" Long

• 1.5" fixed hook blade with guide shoe at the blade point: no damage of the conductor insulation



Insulated Cable Cutters

• Operating voltage: 1000V AC – 1500V DC

Item#	Length	Capacity
CTU-MO-67501	7"	15mm
CTU-MO-67502	9"	18mm





9-Pc Insulated **Pliers/Cutters Tray Set**

- 9" Lineman's with crimper
- 8" Lineman's • 6.3" & 8"Long nose
- 6.3" & 8" Diagonal cutters
- 6.3" Stripping pliers
- 7" Crimp pliers
- 8" Cable cutter







KLE-11054EINS

1000 Volt-Rated Insulated Wire Stripper/Cutter, 8"

- Strips and cuts: 8-16 AWG solid, 0-18 AWG stranded
- Screw shearing: #6-32 and #8-32



Item #	Description
Diagonal Cutting	Pliers
CRE-6DIAGVDE	6" 1000V Insulated Diagonal Pliers
CRE-7DIAGVDE	7" 1000V Insulated Diagonal Pliers
Long Nose Pliers	
CRE-6LNVDE	6" 1000V Insulated Long Nose Pliers
CRE-8LNVDE	8" 1000V Insulated Long Nose Pliers
Linesman Pliers	
CRE-6LMVDE	6" 1000V Insulated Linesman Pliers
CRE-7LMVDE	7" 1000V Insulated Linesman Pliers
CRE-8LMVDE	8" 1000V Insulated Linesman Pliers
Wire Stripper Pl	iers
CRE-6WSVDE	6" 1000V Insulated Wire Stripper Pliers








13-Pc Insulated **Open End Wrench Tray Set**

• 8mm, 10mm, 11mm, 12mm, 13mm, 14mm, 15mm, 16mm, 17mm, 18mm, 19mm, 22mm, 24mm

• Certified to 1000 Volt AC





Item #	Description
WIH-75220	8" Insulated Tweezers, Serrated, Straight Blunt Tip
WIH-75302	6" Insulated Tweezers, Serrated, Angled Fine Tip
WIH-75304	8" Insulated Tweezers, Serrated, Angled Blunt Tip



EV & HEV Service Tools & Equipment





CTU-M07582D

Entirely Insulated Magnet on Flexible Handle

- Magnet diameter: 0.24" (6mm)
- Maximum load to the magnet: 1.65 lbs (0.750 kg)
- Certified to 1000 Volt AC or 1500 Volt DC





CTU-ALPV-XL-D

Locking Cover for Steering Wheel

- Up to 24.4" (62 cm)
- Transparent pocket (A5 size) allows to display a personalized
- message during the lock-out procedure
- Strap closure at the back with 10mm metal eyelets for inserting a padlock and self-gripping part





CTU-MP-11/11

Insulating Mat - Class 0

- Insulating mat for live line work and dead work
- 3.3 ft. x 3.3 ft. (1m x 1m) Thickness: 2.2mm
- Operating voltage: 1000V AC 1500V DC
- Low temperature folding test at -40 °C
- Operating temp.: -40°C to +55°C





CTU-MP-220

Orange Insulating Blanket - Class 0

- Used as protection for workers operating on live lines, live parts or in the vicinity of live parts
- 3.3 ft. x 3.3 ft. (1m x 1m)
- Thickness: 1.2mm
- Operating voltage: 1000V AC 1500V DC
- Resistance to bending at very low temperature (-40°C)
- Oil resistance and high puncture resistance
- Operating temp.: -40°C to +55°C






KNI-98 67 05

20" x 20" Rubber Mat. 1000V Insulated

- For added protection when working live or close to live parts
- Thickness: 1/16" (1.58mm)







Item #

CTU-MP-123

CTU-MP-123/1

CTU-MP-123/2

Insulating Blanket - Class 0

- Used as protection for workers operating on live parts or in the
- Operating voltage: 1,000V AC 1,500V DC
- · Acid and oil resistance
- High puncture resistance
- fixation or fitting with another blanket
- Operating temp. range: -40°C to +55°C

- vicinity of live parts

- Gripping tape ("Velcro" type) all around the blanket for

CTU-KIT-RC-TST1

Protective Equipment Kit for Live Conductors and Connectors

- Operating voltage: 1000V AC 1500V DC Includes:
- (1) Insulating blanket, Class 0, 1m x 1m (#MP-220) • (4) Insulating clamps for blanket
- (#MP-627-D)
- (3) Insulating caps, Class 0, 30mm x 120mm (#MP-635/30-D)
- (3) Insulating caps, Class 0, 60mm x 180mm (#MP-635/60-D)



Description

14" x 26" (0.36m x 0.66m)

19.5" x 35.5" (0.5m x 0.9m)


31.5" x 47" (0.8m x 1.2m)

Each item in this set can also be purchased separately.

Each item in this set can also

CTU-KIT-VEH

Delineation Kit for of Electric & Hybrid



- (6) Red and white ballasted boundary posts (#AL-323)
- (1) Plastic chain with red and white links, 25m (#AL-31/25)
- (2) Plastic signs, 450mm x 150mm (#AP-72)

CTU-ACA-10

"Electric Hazard" Warning Pyramid with Magnetic Base

• Cardboard cone, 5.5" (140mm) side

CTU-AT-5005

Safety Adhesive Signaling/Delineation Tape

- Self-adhesive PVC
- 2" x 328 ft. (50mm x 100m)







KLEIN

EV & HEV Service Tools & Equipment







Detex[™] Low Voltage Detector

- Operating voltage: 12-690V AC /12-750V DC
- (7) Thresholds
- Frequency: 50-60 Hz
- Continuity: 200 Ω
- Polarity
- Unipolar phase identification
- Phase indication
- Completely modular and adjustable to eclipse sockets







PWP-VT750LCD

Two-Pole Voltage Tester for Electric and Hybrid Vehicles

- Safety rated at 1000V CAT III, 600V CAT IV
- Automatically selects the correct voltage range
- AC/DC Volts: 750V
- Resistance: 0~2,000Ω Frequency: 30Hz~999Hz
- Continuity beeper: ≤600KΩ Diode test: 0.3V~0.9V
- Single phase test voltage: 100~750V



FLU-5066006

Fluke 1507 - Insulation Resistance Tester

- Rugged, compact advanced insulation resistance tester for electrical contractors and industrial and commercial electricians
- Automatically calculates Polarization Index and Dielectric Absorption Ratio
- · Makes repetitive tests simple and easy with a Compare (Pass/Fail) function
- Voltage AC/DC: 0.1V to 600V
- Continuity: 200 mA
- Resistance: 0.01 Ω to 20.00 k Ω
- Insulation test range: $0.01 \, M\Omega$ to $10 \, G\Omega$
- Insulation test voltages: 50V, 100V, 250V, 500V, 1000V



FLUKE



FLU-4691215

Fluke 1587 FC -

Insulation Tester & True RMS Multimeter • Fluke Connect®-enabled

- PI/DAR timed ratio tests
- Insulation test range: 0.01 M Ω to 2 G Ω
- Insulation test voltages: 50V, 100V, 250V, 500V, 1000V
- Voltage AC/DC: 1000V
- · Capacitance, diode test, temperature, Min/Max, and frequency
- Continuity: 200 mA
- Resistance: 50 MΩ



KLE-ET600

Insulation Resistance Tester with Multimeter Test Functions

- Test voltages: 125V, 250V, 500V, 1000V
- Insulation resistance: 4000MΩ
- Test lock
- Live circuit detection
- AC/DC voltage: 1000V
- Resistance: 4kΩ
- True RMS Audible continuity
- Auto-ranging, Auto-Zero
- Data hold Min/Max value
- Bar graph
- CAT IV 600V and CAT III 1000V



PWP-PPDMM

Automotive Digital Multimeter

- Hybrid safe CAT-IV 600V
- · Digital Volt and Ohmmeter for circuit testing Measures:
- AC/DC Voltage to 600V
- Current to 10 Amps
- Resistance/Diode/Continuity to 60M Ohms
- Capacitance: 0.0001μF to 60,000μF
- Frequency, duty cycle
- Temperature from -4°F to 1,832°F (-20°C to 1,000°C)
- Data hold, Min/Max capture, relative measurement



BOSCH

BSD-F00E9001013CM

MMD 540H Hybrid Digital Multimeter

- CAT III (1,000V) safety rating for hybrid vehicle circuits
- Peak, Min/Max readings as fast as 1 millisecond
- Higher amperage test ranges, up to 20 Amps
- Inductive RPM clamp for conventional and DIS ignition systems
- Fused diagnostic test leads for safe trouble shooting (up to 20 amps)
- K-Type thermocouple for quick temperature measurement
- Trilingual users manual on CD





ESI-595

Automotive Meter with PC Interface

- Safe for use on hybrids and EV's
- CAT III 1.000 Volt
- Max/Min function
- DC Volts: 1000V AC Volts: 750V
- AC/DC Amps: 20A
- Ohms: 40MΩ Capacitance: 100uF
- RPM 4: 0-4,000 RPM, 12,000 RPM x 10
- RPM2/DIS: 0-4,000 RPM, 6,000 RPM x 10
- Dwell: 1, 2, 3, 4, 5, 6, 8, 10, & 12 cylinder • Frequency: 0-5Hz, 50Hz, 500Hz, 5kHz, 30kHz
- Duty cycle: 0.1% 99.9%
- mS pulse width: 2.0mS 10.0mS
- Temperature: -4°F to 1400°F, -20°C to 760°C
- Continuity Diode test





EV & HEV Service Tools & Equipment



TBQ-4JPT

4-Pc Lifting Jack Pads for Tesla Models S, 3, X, Y

- These rubber pads are positioned under the designated Tesla lift points to prevent damage to the battery or the side rails of the vehicle when lifting
- Load capacity (4 pads): 5 ton



(norco

NRC-72850A

2,500 Lbs Capacity Powertrain Lift/Work Table

- Handles powertrain components like engines, transmissions, transaxle assemblies, rear ends and large electric vehicle batteries
- Air/hydraulic foot pump
- Lift height: 31" to 78"
- Overall dim.: 50" L x 33" W x 35" H
- Table size: 19" x 36"
- Saddle tilt: 15°
- Weight: 665 lbs





OTC-1585A

1,250 Lbs Capacity **Power Train Lift with Tilting Plate**

- Ideal for engine and transaxle service
- Height range: 29-1/2" to 68-1/2"
- Weight: 372 lbs





ATD-7478

2,500 Lbs Capacity Powertrain Lifting Table

- Designed to handle heavy engine, drive axle assemblies, transmissions, electric vehicle batteries and other vehicle components
- Air/hydraulic foot pump
- Capacity @ 100 psi: 2,500 lbs
- Lifting range: 33" 77
- Table size: 19.7" x 32"
- Table tilt: +/- 11°
- Overall dim.: 48" x 33" x 33"
- Weight: 586 lbs









A/C Recover, Recycle, Recharge Machines

ARCTIC COMMANDER	MTC-COMMANDER4000	MTC-COMMANDER3000
FEATURES	Automatic R1234YF & HYBRID	Automatic R134A & HYBRID
8" Colour Command Center with Touch Screen	•	
Automatic and Manual Procedures	•	
Refrigerant Database		
Automatic Vacuum Leak Test: Programmable	-	•
Auto Oil Discharge		
Auto and Manual Air Purge		
Auto Filter and Full Tank Alarm		
Low Refrigerant Alarm		
Auto Oil Injection		
Thermal Printer		
Hose Flushing		
Vehicle A/C System Flushing		
Tank Heater		
6 CFM Vacuum Pump		
Refrigerant Identifier		
On-Board Unit Conversion Calculator		
Self-Diagnostic Check		
Wi-Fi Capable		

ROBINAIR

ROB-34788NI-H

Fully Automatic R-134A Refrigerant Recovery, Recycling, and Recharging Machine for Hybrid & Non-Hybrid Vehicles

- Connection: Wi-Fi capable (optional kit)
- Display: 5" x 9" graphical display
- 1.5 CFM vacuum pump
- A/C component flushing
- Vacuum leak test Automatic air purge
- Automatic oil drain
- Automatic refrigerant refill • Refrigerant & oil database: optional
- Service record storage
- Refrigerant management
- Certification: SAE J2788







EV & HEV Service Tools & Equipment

TRACERLINE®





HBF-TPOPUV20EV

POE-Based EV A/C Dye UV Leak Detection Kit

- Compatible with R-1234yf & R-134a
- TP9815EV-P3: (3) 0.25 oz (7 ml) cartridges of Electric Vehicle POE-based A/C Dye Mini-EZ™ cartridges
 • TP9845: EZ-Ject™ dye injector
- TP-9813: R-134a coupler and purge fitting
- TP19: fluorescent dye cleaner
- TP9831: R-1234yf adapter



TRACERLINE®



POE-Based EV A/C Dye MINI-EZ™ Injection Kit

- Compatible with R-1234yf & R-134a
- TP9815EV-P3: (3) 0.25 oz (7 ml) cartridges of Electric Vehicle POE-based A/C Dye Mini-EZ™ cartridges
- **TP9845:** EZ-Ject™ dye injector
- TP-9813: R-134a coupler and purge fitting
- TP9831: R-1234yf adapter
- Services up to 3 vehicles





TRACERLINE®





HBF-TP9815EV-P3

POE-Based EV A/C Dye MINI-EZ™ Cartridges

- Compatible with R-1234vf & R-134a
- (3) 0.25 oz (7 ml) single-dose Electric Vehicle A/C dye cartridges
- Services up to 3 vehicles



TRACERLINE®





Electric Vehicle A/C Oil & A/C Oil + UV Dye

- Compatible with R-1234yf & R-134a

• Services 1 vehic	le
Item#	Description
HBF-TP100EV-5	5 oz (148 ml) Foil Pouch with POE-Based A/C Oil
HBF-TP100EVD-5	5 oz (148 ml) Foil Pouch with POE-Based A/C Oil + UV Fluorescent Dye





TP100EVD-5

TRACERLINE®



HBF-TP9812-BX

Hybrid Vehicle/ESTER MINI-EZ™ Universal A/C Dye Injection Kit

- Uniquely blended with special additives for hybrid A/C systems
- Compatible with R-1234yf & R-134a
- **TP9811-P3:** (3) 0.25 oz (7 ml) single-dose Hybrid Vehicle/Ester A/C dye cartridges
- **TP9845:** EZ-Ject™ dye injector
- TP-9813: R-134a coupler and purge fitting
- TP9831: R-1234yf adapter
- Services up to 3 vehicles

TRACERLINE®





Hybrid Vehicle/ESTER MINI-EZ™ Universal A/C Dye

- Uniquely blended with special additives for hybrid A/C systems • Compatible with R-1234yf & R-134a
- (3) 0.25 oz (7 ml) single-dose Hybrid Vehicle/Ester A/C dye cartridges
- Services up to 3 vehicles

TRACERLINE®



Hybrid Vehicle /ESTER A/C Oil & A/C Oil + UV Dye

- Compatible with R-1234yf & R-134a
- Services 1 vehicle
- Viscosity: 32 cSt/Ester

V100001ty: 02 00t/ 20t01				
Item #	Description			
HBF-TP32EH-5	5 oz (148 ml) Foil Pouch with A/C Oil			
HBF-TP32EHD-5	5 oz (148 ml) Foil Pouch with A/C Oil + UV Dye			







TP32EHD-5



EV & HEV Service Tools & Equipment

AUTEL MAXICHARGER



Mobile device or computer not included



AC Wallbox Level 2 Electric Vehicle Chargers

- Compatible with all EV & plug-in hybrid vehicles
- Indoor/Outdoor use, built to withstand any type of climate
- Level 2 chargers require 240V
- Up to 9X faster charge
- Dimensions: 7.36" x 13.22"
- Generous 25-foot cable
- Safe & secure access control
- Connect by Wi-Fi, Bluetooth, Ethernet, CAN, RS485 or 4G Cellular (4G Cellular works with the Commercial unit only)
- 4 LED lights on face of charger clearly indicate the status of your charger
- 24/7 customer support line
- Automatic firmware updates
- Includes 3 year warranty

• AC WALLBOX HOME Smart Charging:

The Autel Mobile Charge App enables remote start, stop, monitoring and scheduling. Available at App Store or Google Play.

• AC WALLBOX COMMERCIAL Smart Charging:

Smart charger capabilities with Autel Cloud Charging Portal to monitor and manage all chargers and control access from your computer or mobile device. This allows you to control station access, pricing along with hours of operation. Smart features like demand response and dynamic load balancing help with reducing operation costs.

Product	Item #	Power Output	Power Supply	Holster	Front Face	Wi-Fi	Mobile App	Internet-Based Commercial Portal
	AUL-MC40AP14S HOME	Adjustable up to 40 Amps 9.6 kW	NEMA 14-50 Plug	Separate	Indicator Lights Only	~	~	
	AUL-MC40AP6S HOME	Adjustable up to 40 Amps 9.6 kW	NEMA 6-50 Plug	Separate	Indicator Lights Only	~	~	
	AUL-MC50AHS HOME	Adjustable up to 50 Amps 12 kW	HARDWIRED*	Separate	Indicator Lights Only	~	~	
	AUL-MC40AP14I HOME	Adjustable up to 40 Amps 9.6 kW	NEMA 14-50 Plug	In-Body	Indicator Lights Only	~	~	
	AUL-MC40AP6I HOME	Adjustable up to 40 Amps 9.6 kW	NEMA 6-50 Plug	In-Body	Indicator Lights Only	~	~	
B (/	AUL-MC50AHI HOME	Adjustable up to 50 Amps 12 kW	HARDWIRED*	In-Body	Indicator Lights Only	~	~	
9,	AUL-MCC50AHI COMMERCIAL	Adjustable up to 50 Amps 12 kW & 72 KM of range per hour	HARDWIRED*	In-Body	5" Interactive LCD Touchscreen	~		~

^{*}Recommended hardwire for outdoor installation




Made in



Personal Protective Equipment

CTU-CS452 **Rescue Stick with Insulated Permanent Hook**

- 45 kV
- 1.65m long
- Includes wall brackets (#CI-06-D)



CTU-CZ-EV-RESC

Rescue Wall Kit for Automotive Maintenance and Body Repair Shops

- (1) Rescue stick with insulated hook (#CS-45/2)
- (#CGM-0-10)
- (1) Fire extinguisher for Li-Ion battery (#CD-307)
- Wall mounting accessories





CTU-KIT-VEH-DEP

Head and Hand Protection Kit for Towing Services for Electric and Hybrid Vehicles and Machines

- (1) Arc-Flash protective faceshield with headband and a storage bag (#MO-286)
- (1) Pair of short insulating gloves (28cm), Class 0, 1000V AC / 1500V DC, size 10 (#CG-0-10-R-28)
- (1) Pair of cotton under-gloves (#CG-80-H)
- (1) Pair of short leather overgloves, size 10 (#CG-984-10)
- (1) Bag for protection and storage of gloves (#CG-36-1)
- (40) "DAMAGED VEHICLE" removable stickers (#AT-81)
- (1) Non-conducting safety padlock (#PP-6-38-R-Z)
- (10) Safety Tag-Out badges with warning sign (#AP-460)
- (1) Storage bag (#MO-42/2)

High-Visibility Multi-Risk Parka with Hood for Protection Against Electric Arc

· Protection against thermal hazards of an electric arc, heat and flames, rain protection, anti-static, small splash of liquid chemicals

· Central zip with flap, adjustable belt at the waist • 2 Chest pockets and 2 hip pockets

Item #	Size
CTU-M-883374	S
CTU-M-883377	M
CTU-M-883378	L
CTU-M-883379	XL
CTU-M-883380	2XL
CTU-M-883381	3XL









CAT'ARC Multi-Risk Switching Jacket to Protect Against an Electric Arc

- Designed to be worn on top of the usual clothing
- Adjustable hood
- To be worn with a visor or a helmet
- Velcro® central fastening along the entire length
- Back length of 47" (121 cm)
- · Visor, insulated gloves and shoes sold separately


Item#	Size
CTU-AFG-2300-S	S
CTU-AFG-2300-L	L
CTU-AFG-2300-2XL	2XL
CTU-AFG-2300-4XL	4XL



CTU-MV-99-INSD

Orange Elastomer Insulating Apron - Class 0

- Operating voltage: 1000V AČ - 1500V DC
- · Adjustable belt strap with plastic lock
- · Acid and oil resistant
- High resistance to perforation
- Can be folded at very low temperature (-40°C)
- Insulator's H x W: 65 cm x 50 cm
- Thickness: 1 2mm





Safety Shoes with Insulating Sole - Class 0

- Operating voltage: 1000V AC 1500V DC
- Low-cut and textile type shoe
- Slip resistant sole
- Leather reinforcements at the front and the back
- Extra perspiration-resistant, anti-bacterial lining

em #	Size
ГU-MV-226-40	40
ГU-MV-226-41	41
ГU-MV-226-42	42
TU-MV-226-43	43
ΓU-MV-226-44	44
TU-MV-226-45	45
ГU-MV-226-46	46
ГU-MV-226-47	47

Insulating Overboots - Class 1

- Operating voltage: 7,500V AC / 11,250V DC
- Meets the requirements of ASTM 1117 (20kV)
- Ideal for temporary and frequent use • Fit perfectly over safety shoes
- 100% waterproof
- Fuel and oil resistant rubber sole promoting a superior slip resistance
- Sole pattern design avoids clogging and catching on rungs when climbing ladders
- Hot contact resistant sole to 300°C for 60 seconds
- Quick and easy to wear & remove; kick-off lug for hands free removal
- · Comfortable, durable and lightweight







Size



75mm / 3"

88mm / 3.5"

101mm / 4"

126mm / 5"

113mm / 4.5"

140mm / 5.5"

Personal Protective Equipment

CTU-MO-286

Arc-Flash Protective Face Shield with Headband for Electrician

- Protective face shield against thermal effect of short-circuit electric arcs
- To wear without a helmet
- Ratchet head adjustment
- Anti-scratch and anti-fogging treatments
- Visor height: 8" (20.5 cm)







Electrical Insulating Gloves, Red - Class 0

- Includes the dielectric and conformity certificate
- Rolled edges for more comfort
- Material: Natural Latex
- Length: 14"

Item #	Size
CTU-GI-01408-RRI	8 (M)
CTU-GI-01409-RRI	9 (L)
CTU-GI-01410-RRI	10 (XL)
CTU-GI-01411-RRI	11 (2XL)



Leather Overgloves for Low Voltage Insulating Gloves

- Ensure mechanical protection for insulating gloves (Class 00 & 0)
- Resistant to flame and contact heat of 100°C for 10 seconds according to EN 407
- Velcro® adjustable cuffs

voioro aajaot	abio odiri
Item #	Size
CTU-CG-981-08	8
CTU-CG-981-09	9
CTU-CG-981-10	10
CTU-CG-981-11	11



Undergloves for Insulating Gloves

- Comfortable fit, washable undergloves improve the comfort of use and hygiene of insulating gloves
- Helps protect from Latex allergies

Item #	Fits Size
CTU-CG-80-F	8
CTU-CG-80-H	9, 10, 11



CTU-CG-36-1

Storage Case for Insulating Gloves - Class 00, 0, 1

- Made of repellent reinforced fabric for the transportation of insulating gloves in vehicles and tool boxes
- Rear loop for belt carriage and transparent pocket for instructions or identification
- Velcro fastening
- 16.5" x 7" x 2"



100% Natural Rubber Electrical Insulating Gloves

ANSELL GLOVE

SIZING CHART

your hand from the

base of your index

knuckles.

Measure the width of

finger and across your

Ansell

- 11" long gloves
- Ergonomically-designed hand-at-rest shape for less hand fatigue
- Generous flared cuff allows room for clothing and improves ventilation
- Exceeds ASTM D120 standards for tensile strength, elongation, tear & puncture resistance
- Product meets all applicable ASTM, NFPA, OSHA, CSA and EN standards

Red Gloves, Class 0

Max. use voltage AC/DC 1,000 / 1,500 Volt

Item#	Size
ANS-MIA011R7	7
ANS-MIA011R8	8
ANS-MIA011R9	9
ANS-MIA011R10	10
ANS-MIA011R11	11
ANS-MIA011R12	12

Yellow Gloves, Class 0

7 / S

8 / M

10 / XL

11 / 2XL

12 / 3XL

Max. use voltage AC/DC 1,000 / 1,500 Volt

Item#	Size
ANS-51202	7
ANS-51203	8
ANS-51204	9
ANS-51205	10
ANS-51206	11
ANS-51207	12

10" Industrial Leather Protector Gloves

-Class 00, 0

- Should always be worn over Rubber Insulating Gloves to meet OSHA and ASTM standards to provide mechanical protection against cuts, abrasions and punctures
- SIZING: These leather gloves should be ordered in the same size as the Rubber Electrical Insulating Gloves

Item #	Size
ANS-RIGLVCVR070	7
ANS-RIGLVCVR080	8
ANS-RIGLVCVR090	9
ANS-RIGLVCVR100	10
ANS-RIGLVCVR110	11
ANS-RIGLVCVR120	12



Protective Bag with Clip

 Canvas glove bag is designed for use with Electrical Insulating Gloves

Item#	Size
ANS-RIGCVSBAG14	14"
ANS-RIGCVSBAG16	16"







g2stobeq.ca

Please contact your local Distributor for pricing and availability.





AUL-EVDIAGKIT

EV Diagnostics Upgrade Kit

- Includes EVDiag Box, software, and adapters for specific vehicles to achieve battery packs diagnostics for electric vehicles
- Compatible with the MaxiSYS Ultra, MaxiSYS Ultra ADAS, MaxiSYS MS919, and MaxiSYS MS909

BATTERY PACK DIAGNOSTICS

- In-depth battery pack diagnostics for the most popular EV vehicles on the market including BMW, Tesla, and VW/Audi
- State of Charge and State of Health analysis for true battery condition





MS909EV & MSULTRAEV INTELLIGENT EV DIAGNOSTICS



Intelligent EV Diagnostics Tablets

- Secure high-voltage system testing and analysis
- Advanced diagnostics for U.S., European and Asian electric, gas & diesel, and hybrid vehicles

	AUL-MS909EV	AUL-MSULTRAEV
HARDWARE		
Wireless Vehicle Connection	Bluetooth MaxiFash VCI	Bluetooth MaxiFash VCMI
Colour Touchscreen	10" LCD	13" LCD
Processor	2.2 GHz + 1.8 GHz Octa-Core	2.2 GHz + 1.8 GHz Octa-Core
Memory / RAM	128GB SSD / 4GB RAM	256GB SSD / 4GB RAM
Docking Station		Included
EVDiag Box	Included	Included
SOFTWARE		
Operating System	ANDROID 10.0	ANDROID 7.0
Split Screen Display		View Multiple Functions At Once
High-Voltage System Diagnostics	Diagrams of High-Voltage System Block	Diagrams of High-Voltage System Block
Battery Pack Diagnostics	SOC and SOH Analysis	SOC and SOH Analysis
Advanced VCMI 5-in-1 Device		VCI, Oscilloscope, Multimeter, Waveform Generator, CAN Bus Check
Secure Gateway Access	Authorized FCA Access with AutoAuth Account	Authorized FCA Access with AutoAuth Account
FEATURES		
Service Resets	36 Service Features	36 Service Features
Diesel (Light & Medium Duty)	Reset Diesel Emissions	Reset Diesel Emissions